SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Husqvarna 4-Stroke Oil 5W-30
Registration number	-
Synonyms	None.
Product code	577 41 92-03 (0,6L), 577 41 91-03 (1,4L)
Issue date	31-August-2012
Version number	01
Revision date	-
Supersedes date	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Lubrication of 4-stroke engine.
Uses advised against	Use in accordance with supplier's recommendations.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Husqvarna AB
Address	Drottninggatan 2
Telephone	036-14 65 00
e-mail	sds.info@husqvarna.se
Contact person	Accessory Department

1.4. Emergency telephone number	+1-760-476-3961 (Access code 333721)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Hazard summary

Physical hazards	Not classified for physical hazards.
Health hazards	Not classified for health hazards.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	Direct contact with eyes may cause temporary irritation. May form vapours or oil mists during mechanical action or at elevated temperatures which may be irritating to respiratory tract. Prolonged skin contact may cause dermatitis.
Main symptoms	May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory system and cause coughing.

2.2. Label elements

Label according to Directive 67/548/EEC or 1999/45/EC as amended

R-phrases	Not available.
S-phrases	Not available.
Authorization number	Not available.
Supplemental label information	Not applicable.
2.3. Other hazards	Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	50 - 75	72623-87-1 276-738-4	-	649-483-00-5	
Classification: **DSD:** - **CLP:** -					
Highly refined mineral oil (DMSO-extract < 3% IP 346)	15 - 20	- -	-	-	
Classification: **DSD:** - **CLP:** -					
Bis(nonylphenyl)amine	< 25	36878-20-3 253-249-4	-	-	
Classification: **DSD:** R53 **CLP:** Aquatic Chronic 4;H413					

CLP: Regulation No. 1272/2008.
DSD: Directive 67/548/EEC.
#: This substance has been assigned Community workplace exposure limit(s).

Composition comments The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Call a physician if symptoms develop or persist.

Skin contact Wash with soap and water. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions. If high pressure injection under the skin occurs, always seek medical attention.

Eye contact Flush eyes immediately with large amounts of water. Remove any contact lenses and open eyelids wide apart. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory system and cause coughing.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Symptoms may be delayed. HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue and open wound dressing.

SECTION 5: Firefighting measures

General fire hazards Heating may generate vapors which may form explosive vapor/air mixtures. Material will float and can be re-ignited on surface of water.

5.1. Extinguishing media

Suitable extinguishing media Foam. Dry powder. Carbon dioxide (CO2). Water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture By heating and fire, irritating vapours/gases may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Special fire fighting procedures	Move container from fire area if it can be done without risk. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). In case of spills, beware of slippery floors and surfaces. Wear protective clothing as described in section 8 of this safety data sheet.
For emergency responders	Wear protective clothing as described in Section 8 of this safety data sheet.
6.2. Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not allow to enter drains, sewers or watercourses. Environmental manager must be informed of all major releases.
6.3. Methods and material for containment and cleaning up	Remove sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Wash area with soap and water. Small Spills: Wipe up spilled material and place in a suitable container for disposal. Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Use only in well-ventilated areas. Avoid inhalation of oil mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Do not eat, drink or smoke when using the product. Be aware of potential for surfaces to become slippery. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Keep away from ignition, flame and heat sources. Store in a cool, dry, well-ventilated place. Store away from incompatible materials.
7.3. Specific end use(s)	Lubrication of 4-stroke engine.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	5 mg/m3

Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	Ceiling	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

Denmark. Exposure Limit Values

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TLV	1 mg/m3	Mist.

Finland. Workplace Exposure Limits

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	5 mg/m3	Mist.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	5 mg/m3	Mist.

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	Ceiling	5 mg/m3	Mist.

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	1 mg/m3	Mist.

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	0,2 mg/m3	Inhalable fraction.

Italy. OELs

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	5 mg/m3	Inhalable fraction.

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	5 mg/m3

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements (Hygiene Norm HN 23:2007)

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.

Netherlands. OELs (binding)

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TWA	5 mg/m3	Mist.

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	TLV	1 mg/m3	Mist.

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	10 mg/m3
	TWA	5 mg/m3

Spain. Occupational Exposure Limits

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Sweden. Occupational Exposure Limit Values

Components	Type	Value	Form
Highly refined mineral oil (DMSO-extract < 3% IP 346) (CAS -)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL)

Components	Type	Route	Value	Form
Bis(nonylphenyl)amine (CAS 36878-20-3)	Workers	Dermal	0,62 mg/kg/24h	
		Inhalation	4,37 mg/m3	

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
Bis(nonylphenyl)amine (CAS 36878-20-3)	Aqua (freshwater)	Water	0,1 mg/l	
	Aqua (intermittent releases)	Water	1 mg/l	
	Aqua (marine water)	Water	0,01 mg/l	
	Sediment (freshwater)	Not applicable	132000 mg/kg	
	Sediment (marine water)	Not applicable	13200 mg/kg	
	Sewage Treatment Plant	Not applicable	1 mg/l	
	Soil	Soil	263000 mg/kg	

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Use explosion-proof equipment. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

General information Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Risk of contact: Wear safety glasses with side shields (or goggles).

Skin protection	
- Hand protection	Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
- Other	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Respiratory protection	In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P2) can be used. Wear air-supplied mask in confined areas. Seek advice from local supervisor.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Private clothes and working clothes should be kept separately.
Environmental exposure controls	Environmental manager must be informed of all major spillages.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Brown liquid.
Physical state	Liquid.
Form	Liquid.
Colour	Brown.
Odour	Slight.
Odour threshold	Not available.
pH	8
Melting point/freezing point	< -36 °C (< -32,8 °F)
Initial boiling point and boiling range	> 300 °C (> 572 °F)
Flash point	> 200 °C (> 392 °F) Open cup (ASTM D 92)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	< 0,01 kPa (20 °C)
Vapour density	Not available.
Relative density	0,852 (Water = 1)
Solubility(ies)	Immiscible in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 300 °C (> 572 °F)
Decomposition temperature	> 300 °C (> 572 °F)
Viscosity	11,3 cSt (20 °C) (100 °C (212 °F)) 65,5 cSt (40 °C (104 °F))
Explosive properties	Not available.
Oxidizing properties	Not oxidizing.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Heat, sparks, flames, elevated temperatures. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.

10.6. Hazardous decomposition products	By heating and fire, irritating vapours/gases may be formed. Carbon oxides. Nitrogen oxides.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion	Ingestion may cause irritation and malaise. Ingestion may result in vomiting; aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis.
Inhalation	In high concentrations, mists/vapors may irritate throat and respiratory system and cause coughing.
Skin contact	Prolonged or repeated contact may dry skin and cause dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms	May cause eye irritation on direct contact. Defatting of the skin. Dermatitis. Ingestion may cause irritation and malaise. In high concentrations, mists/vapors may irritate throat and respiratory system and cause coughing.

11.1. Information on toxicological effects

Acute toxicity	May cause discomfort if swallowed.
Skin corrosion/irritation	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Serious eye damage/irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitisation	No data available.
Skin sensitisation	No data available.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classified.
Reproductive toxicity	No data available.
Specific target organ toxicity - single exposure	High concentrations: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	No data available.
Aspiration hazard	Not classified, however droplets of the product may be aspirated into the lungs through ingestion or vomiting and may cause a serious chemical pneumonia.
Mixture versus substance information	Not available.
Other information	No other specific acute or chronic health impact noted.

SECTION 12: Ecological information

12.1. Toxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
12.2. Persistence and degradability	The product is expected to be biodegradable.
12.3. Bioaccumulative potential	No data available.
Partition coefficient n-octanol/water (log Kow)	Not available.
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not available.
Mobility in general	The product is insoluble in water. It will spread on the water surface while some of the components will eventually sediment in water systems. The volatile components of the product will spread in the atmosphere.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	Oil spills are generally hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

SECTION 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods.

RID

The product is not covered by international regulation on the transport of dangerous goods.

ADN

The product is not covered by international regulation on the transport of dangerous goods.

IATA

The product is not covered by international regulation on the transport of dangerous goods.

IMDG

The product is not covered by international regulation on the transport of dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorisation

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not regulated.

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Not listed.

Directive 94/33/EC on the protection of young people at work

Not listed.

Other regulations	The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.
National regulations	Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

DNEL: Derived No-Effect Level.
PNEC: Predicted No-Effect Concentration.
PBT: Persistent, bioaccumulative and toxic.
vPvB: Very Persistent and very Bioaccumulative.

References

HSDB® - Hazardous Substances Data Bank
Registry of Toxic Effects of Chemical Substances (RTECS)
ESIS (European chemical Substances Information System)

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R53 May cause long-term adverse effects in the aquatic environment.

H413 - May cause long lasting harmful effects to aquatic life.

Training information

Follow training instructions when handling this material.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.