

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	Husqvarna Power 4
Registration number	-
Synonyms	None.
Product code	589 22 79-01 (1L), 589 95 29-04 (5L), 589 95 59-02 (25L), 589 22 79-40 (200L)
Issue date	25-April-2016
Version number	01
Revision date	-
Supersedes date	-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Petrol for 4-stroke engine.
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier	Husqvarna AB
Address	Drottninggatan 2
Telephone	+46 (0)36-14 65 00
Contact person	Accessory Department
e-mail	sds.info@husqvarna.se
1.4. Emergency telephone number	+1-760-476-3961 (Access code 333721)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

#### Physical hazards

Flammable liquids	Category 1	H224 - Extremely flammable liquid and vapour.
-------------------	------------	---

#### Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

#### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 4	H413 - May cause long lasting harmful effects to aquatic life.
--	------------	--

<b>Hazard summary</b>	May be ignited by heat, sparks or flames. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness. Causes skin irritation. Dangerous for the environment if discharged into watercourses.
-----------------------	--

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

<b>Contains:</b>	Low boiling point naphtha (Gasoline)
------------------	--------------------------------------

#### Hazard pictograms



<b>Signal word</b>	Danger
--------------------	--------

#### Hazard statements

H224	Extremely flammable liquid and vapour.
------	--

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H413	May cause long lasting harmful effects to aquatic life.

## Precautionary statements

### Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapour.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.

### Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.

### Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P235	Keep cool.
P405	Store locked up.

### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information** None.

**2.3. Other hazards** Not a PBT or vPvB substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Naphtha (petroleum), full-range alkylate, butane-contg.	67 - 74	68527-27-5 271-267-0	01-2119471477-29-0018	649-282-00-2	
<b>Classification:</b>	Flam. Liq. 1;H224, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic Chronic 2;H411				
Hydrocarbons, C >= 5, C5-6-Rich; Low boiling point naphtha - unspecified	26 - 33	68476-50-6 270-690-8	01-2119489866-14-0003	649-401-00-8	
<b>Classification:</b>	Flam. Liq. 1;H224, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic Chronic 2;H411				

#### List of abbreviations and symbols that may be used above

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The product is an alkylate gasoline. The following compounds may be present: Benzene (CAS 71-43-2) <0.1% v/v; n-hexane (CAS 110-54-3) <0.5% v/v; aromatic hydrocarbons <0.5% v/v.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

#### General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**4.2. Most important symptoms and effects, both acute and delayed** Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable liquid and vapour.

#### 5.1. Extinguishing media

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Special fire fighting procedures** In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

**For emergency responders** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

**6.2. Environmental precautions** Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

**6.3. Methods and material for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS)

### 7.3. Specific end use(s)

Petrol for 4-stroke engine.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

No exposure limits noted for ingredient(s).

#### Biological limit values

No biological exposure limits noted for the ingredient(s).

#### Recommended monitoring procedures

Follow standard monitoring procedures.

#### Derived no-effect level (DNEL)

Components	Type	Route	Value	Form
Low boiling point naphtha (Gasoline)	Consumer	Inhalation	640 mg/m <sup>3</sup> /15min	Acute exposure local effects
		Inhalation	1200 mg/m <sup>3</sup> /15min	Acute exposure systemic effects
		Inhalation	180 mg/m <sup>3</sup> /24h	Long term exposure local effects
	Workers	Inhalation	1300 mg/m <sup>3</sup> /15min	Acute exposure systemic effects
		Inhalation	1100 mg/m <sup>3</sup> /15min	Acute exposure local effects
		Inhalation	840 mg/m <sup>3</sup> /8h	Long term exposure local effects

#### Predicted no effect concentrations (PNECs)

Not available.

### 8.2. Exposure controls

#### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

##### General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

##### Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

##### Skin protection

##### - Hand protection

Wear appropriate chemical resistant gloves. Select suitable chemical resistant protective gloves (EN 374) with a protective index 6 (>480min permeation time). Polyvinyl alcohol or nitrile-butyl rubber gloves. Suitable gloves can be recommended by the glove supplier.

##### - Other

Wear appropriate chemical resistant clothing.

##### Respiratory protection

Chemical respirator with organic vapour cartridge and full facepiece.

##### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state	Liquid.
Form	Mobile. Liquid.
Colour	Clear.
Odour	Hydrocarbon. Mild.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	30 - 200 °C (86 - 392 °F)
Flash point	< 0 °C (< 32.0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

#### Upper/lower flammability or explosive limits

Flammability limit - lower (%)	7.6 %
Flammability limit - upper (%)	1.4 %
Vapour pressure	50 - 65 kPa (38 °C)
Vapour density	> 3 Air = 1
Relative density	0.68 - 0.72 (15.4 °C)
Solubility(ies)	< 50 µg/l (20 °C)
Partition coefficient (n-octanol/water)	Log Kow: >3
Auto-ignition temperature	400 °C (752 °F) approx.
Decomposition temperature	Not available.
Viscosity	< 1 mm <sup>2</sup> /s (kinematic) (38 °C)
Explosive properties	Not explosive.
Oxidising properties	Not oxidising. Does not meet the criteria as an oxidizer.
9.2. Other information	No relevant additional information available.

## SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
---------------------	--

#### Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

#### 11.1. Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects.
----------------	---

Components	Species	Test results
Low boiling point naphtha (Gasoline) (CAS -)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/l
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.	
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.	
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Mixture versus substance information</b>	No information available.	
<b>Other information</b>	No additional adverse health effects noted.	

## SECTION 12: Ecological information

**12.1. Toxicity** May cause long lasting harmful effects to aquatic life.

Product			Species	Test results
Husqvarna Power 4				
Aquatic				
Algae	NOEC		Pseudokirchneriella subcapitata	100 mg/l, 72 Hours OECD 201, ref. report 081/15
Crustacea	NOEC		Daphnia magna	100 mg/l, 48 Hours OECD 202, ref. report 086/15
Acute				
Algae	EC50		Pseudokirchneriella subcapitata	> 100 mg/l, 72 Hours OECD 201, ref. report 081/15
Crustacea	EC50		Daphnia magna	> 100 mg/l, 48 Hours OECD 202, ref. report 086/15

**12.2. Persistence and degradability** Expected to be inherently biodegradable.

### 12.3. Bioaccumulative potential

**Partition coefficient n-octanol/water (log Kow)**

Husqvarna Power 4 > 3 (Log Kow)

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** The product contains volatile substances, which may spread in the atmosphere.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1203
<b>14.2. UN proper shipping name</b>	GASOLINE
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### RID

<b>14.1. UN number</b>	UN1203
<b>14.2. UN proper shipping name</b>	GASOLINE
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### ADN

<b>14.1. UN number</b>	UN1203
<b>14.2. UN proper shipping name</b>	GASOLINE
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### IATA

<b>14.1. UN number</b>	UN1203
<b>14.2. UN proper shipping name</b>	Gasoline
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>ERG Code</b>	3H
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### IMDG

<b>14.1. UN number</b>	UN1203
<b>14.2. UN proper shipping name</b>	GASOLINE

**14.3. Transport hazard class(es)**

Class 3

Subsidiary risk -

**14.4. Packing group** II

**14.5. Environmental hazards**

Marine pollutant No.

EmS F-E, S-E

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations**

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Not listed.

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

**Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended**

Not listed.

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Not listed.

**Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended**

Hydrocarbons, C  $\geq$  5, C5-6-Rich; Low boiling point naphtha - unspecified (CAS 68476-50-6)

Naphtha (petroleum), full-range alkylate, butane-contg. (CAS 68527-27-5)

**Directive 94/33/EC on the protection of young people at work, as amended**

Hydrocarbons, C  $\geq$  5, C5-6-Rich; Low boiling point naphtha - unspecified (CAS 68476-50-6)

Naphtha (petroleum), full-range alkylate, butane-contg. (CAS 68527-27-5)

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

96/82/EC (Seveso II) Directive; Part 2 (Classified Substances) - Extremely Flammable



**National regulations**

Follow national regulation for work with chemical agents.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended

**15.2. Chemical safety assessment**

Chemical Safety Assessment has been carried out.

**SECTION 16: Other information****List of abbreviations**

PBT: Persistent, bioaccumulative and toxic.  
vPvB: Very Persistent and very Bioaccumulative.  
EC50: Effective Concentration, 50%.  
NOEC: No observed effect concentration.  
CEN: European Committee for Standardisation.  
ECHA registered substances database

**References****Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H224 Extremely flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

Husqvarna AB cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.