

# **SAFETY DATA SHEET**

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Husqvarna 4-Stroke Oil 10W-40

of the mixture

Registration number

Synonyms None.

**Product code** 531 00 92-71 (0,08L), 577 41 97-02 (1,4L)

Issue date 01-March-2018

Version number 01
Revision date Supersedes date -

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lubrication of 4-stroke engine.

**Uses advised against**Use in accordance with supplier's recommendations.

1.3. Details of the supplier of the safety data sheet

Company name Husqvarna AB

Drottninggatan 2

561 82 Huskvarna, Sweden

**Telephone** +46 (0)36-14 65 00 **Contact person** Accessory Department

E-mail sds.info@husqvarnagroup.com

1.4. Emergency telephone

number

+1-760-476-3961 (Access code 333721)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

# Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary

Not classified for health hazards. However, occupational exposure to the mixture or substance(s)

may cause adverse health effects.

### 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.
Signal word None.

**Hazard statements** The mixture does not meet the criteria for classification.

**Precautionary statements** 

PreventionNot assigned.ResponseNot assigned.StorageNot assigned.DisposalNot assigned.

Supplemental label information EUH208 - Contains Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts. May

produce an allergic reaction.

EUH210 - Safety data sheet available on request.

**2.3. Other hazards**Not a PBT or vPvB substance or mixture.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

Husqvarna 4-Stroke Oil 10W-40

SDS UK

### **General information**

Chemical name	%	CAS-No. / EC No.	<b>REACH Registration No.</b>	Index No.	Notes
Distillates (petroleum), solvent-dewaxed heavy paraffinic	80 - 90	64742-65-0 265-169-7	01-2119471299-27	649-474-00-6	
Classification: -					L
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	1 - < 3	68649-42-3 272-028-3	01-2120742271-64	-	
Classification: Skin Irrit. 2;	H315, Eye I	rrit. 2;H319			
Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts	0.1 - 0.3	70024-69-0 274-263-7	01-2119492616-28	-	
Classification: Skin Sens. 1	1B;H317				

### List of abbreviations and symbols that may be used above

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

IP346 method DMSO extract for base oil substances: <3.0%. The full text for all H-statements is **Composition comments** 

displayed in section 16.

### **SECTION 4: First aid measures**

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms

and effects, both acute and

Exposure may cause temporary irritation, redness, or discomfort.

delayed 4.3. Indication of any

immediate medical attention and special treatment needed Treat symptomatically.

# **SECTION 5: Firefighting measures**

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

# **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

Keep unnecessary personnel away.

personnel

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Husqvarna 4-Stroke Oil 10W-40 SDS UK

### 6.3. Methods and material for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

6.4. Reference to other

sections

# **SECTION 7: Handling and storage**

7.1. Precautions for safe

handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid prolonged exposure. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

7.3. Specific end use(s)

Lubrication of 4-stroke engine.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

### Derived no effect levels (DNELs)

### **General Population**

Components Value Asse	sment factor N	Notes
-----------------------	----------------	-------

Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts (CAS 70024-69-0)

Long-term, Local, Dermal 0.513 mg/cm2 Long-term, Systemic, Dermal 1.667 mg/kg bw/day

Long-term, Systemic, Inhalation 2.9 mg/m3

Long-term, Systemic, Oral 0.833 mg/kg bw/day

### **Workers**

#### Assessment factor Notes Components Value

Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts (CAS 70024-69-0)

Long-term, Local, Dermal 1.03 mg/cm2 Long-term, Systemic, Dermal 3.33 mg/kg bw/day 11.75 mg/m3 Long-term, Systemic, Inhalation

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Long-term, Local, Inhalation 5.6 mg/m3

## Predicted no effect concentrations (PNECs)

#### Components Assessment factor Notes Value

Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts (CAS 70024-69-0)

Freshwater 1 mg/l 1 mg/l Marine water Secondary poisoning 16667 mg/kg Sediment (freshwater) 226000 g/kg Sediment (marine water) 226000 g/kg 271000 g/kg 1000 mg/l

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Oral Secondary poisoning 9.33 mg/kg

# 8.2. Exposure controls

# Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

**General information** 

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

SDS UK Issue date: 01-March-2018

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

Liquid. Physical state **Form** Liquid. Colour Brown. Not available. Odour **Odour threshold** Not available. pН Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

range

220.0 °C (428.0 °F) ASTM D92 Flash point

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Not available.

Not available.

Not available.

Vapour pressure Not available. Not available. Vapour density

0.888 Relative density

Insoluble in water. Solubility(ies) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature** Not available. **Viscosity Explosive properties** Not explosive. Not oxidising. Oxidising properties

9.2. Other information

Kinematic viscosity 100 mm2/s (40 °C (104 °F))

-39 °C (-38.2 °F) Pour point

# **SECTION 10: Stability and reactivity**

The product is stable and non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

No hazardous decomposition products are known. 10.6. Hazardous

decomposition products

Husqvarna 4-Stroke Oil 10W-40

Version #: 01 Revision date: -Issue date: 01-March-2018

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

May cause an allergic skin reaction.

Direct contact with eyes may cause temporary irritation. Eye contact

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

**Symptoms** Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity

Components **Species Test Results** 

Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts (CAS 70024-69-0)

**Acute** 

**Dermal** 

LD50 Rabbit > 4000 mg/kg, 24 Hours

Inhalation

Aerosol

LC50 Rat > 1.9 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

**Acute** 

**Dermal** 

LD50 Rabbit > 5000 mg/kg, 24 Hours

Inhalation

Aerosol

LC50 Rat > 5 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

**Acute** 

Dermal

LD50 Rabbit 6965 mg/kg

Inhalation

Rat  $> 5000 \text{ mg/m}^3$ LC50

Oral

LD50 Rat 2154 mg/kg

Skin corrosion/irritation

Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. Respiratory sensitisation

Skin sensitisation Based on available data, the classification criteria are not met. The product contains a small

amount of sensitising substance which may provoke an allergic reaction among sensitive

individuals.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Due to partial or complete lack of data the classification is not possible. Reproductive toxicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard** 

Husqvarna 4-Stroke Oil 10W-40 SDS UK 5/7

Mixture versus substance

information

No information available.

Other information

Prolonged and repeated contact with used oil may cause serious skin diseases, such as

dermatitis and skin cancer.

# **SECTION 12: Ecological information**

**12.1. Toxicity**Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

Components Species Test Results

Benzenesulphonic acid, mono-C16-24-alkyl derivs., calcium salts (CAS 70024-69-0)

Aquatic Acute

Crustacea

EC50 Daphnia magna

> 1000 mg/l, 48 hours

12.2. Persistence and

degradability

The product is expected to be biodegradable.

**12.3. Bioaccumulative potential** No data available. **Partition coefficient** Not available.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT

Not a PBT or vPvB substance or mixture.

and vPvB assessment

**12.6. Other adverse effects**Oil spills are generally hazardous to the environment.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging**Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

**EU waste code**The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

**Special precautions**Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

# ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk

Not established.

according to Annex II of MARPOL 73/78 and the IBC

Code

### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Husqvarna 4-Stroke Oil 10W-40 SDS UK

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed.

### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations

15.2. Chemical safety

assessment

Follow national regulation for work with chemical agents. No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

List of abbreviations

EC50: Effective Concentration 50%. LC50: Lethal Concentration 50%. PBT: Persistent, bioaccumulative, toxic. vPvB: very Persistent, very Bioaccumulative.

References ECHA CHEN

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

**Training information** 

Follow training instructions when handling this material.

Disclaimer

Husqvarna AB cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Husqvarna 4-Stroke Oil 10W-40 SDS UK